

Zistos Tactical System



Tactical Surveillance System

The complete tactical system in a custom carrying case.

System Includes:

- **Detached WalkAbout II™:** 5 inch LCD Display
- **ULC-3.5IR:** Ultra Low Light, Infrared Illuminated BW Camera
- **AP-T9:** 9 foot Telescoping/Articulating Pole
- **AAM:** Audio Module & Headphones
- **R-FNS:** Right Angle Adapter for pole
- **BAT-2:** Two NiMH Rechargeable Batteries
- **WBC:** Battery Charger
- **A-CASE:** Custom Carrying Case
- **WUH:** Universal Chest Harness
- **Sunshade**
- **A/V Cable & Vehicle Power Adapter**

Options:

- **Thermal Cameras:** THC-50D (Dual Mode) or THC-36 (Thermal only)
- **Videoscope Kit:** VSK4-BW (BW) or VSK4 (color)
- **Robotic Camera Kit:** ZRS-XT, ZRS-IR or ZRS2
- **Through-the-Wall Cams:** TTW (no audio) or TWA (with audio)
- **Under the Door Camera Kit:** ZDV-CP (Dual View) or ZSV-CP (Single View)
- **Baton :** 0.6M (2 ft) pole B-FNS
- **D-cell Battery Adapter :** D-BAT
- **Consult the factory for wireless options or ToughGrabber**

Zistos Tactical System



Tactical System Includes

9- Foot Telescoping Pole



Three section (2 internal aluminum/1 external fiberglass with foam grip), rugged, break-proof, easy grip pole with twist collars for each section.

- Mechanical pull cable system operated by an easy-to-use twist handle. Camera range of $\pm 90^\circ$ with detents. Twist collar allows camera angle to be locked at any position.
- 4 ft. 3 in. retracted/8 ft. 7 in. extended/6.4 lbs

Part Number AP-T9

Infrared Camera



Ultra low light, infrared illuminated camera in submersible enclosure with hard-coated window.

- 16 IR (invisible) LEDs, B/W camera, 380K pixels (438K/PAL), 0.00003 lux, 92° FOV
- 2.5in. D x 3.5 in. L/0.4 lbs

Part Number ULC-3.5IR

Detached Walkabout II



5-inch display (960 dots H x 234 lines V) with rubber encapsulated aluminum case for shock resistance and weatherproofing.

- LCD Controls: Brightness, Contrast, Color, Tint, OFF/Mirror left/right & up/down
- Base Controls & Indicators: On/Off; LED intensity; Low battery
- Mounting on vest, belt or harness; detached display can also be hand held
- Auto switches between NTSC or PAL
- 12VDC charging from either power supply or vehicle adapter
- NiMH, 7.2V, 2.7AH batteries with charge/discharge time of 2 hrs. when fully discharged/2 hrs. with LEDs off
- Operating Temperature: -20°C to 70°C
- Connections: Camera (pole), A/V output, DC input (7.2V to 12V)
- 6.5 W x 7.0 H x 2.2 inches D/2.1 lbs (LCD); 5.0 W x 3.5 H x 3.5 inches D/2 lbs (Base)

Part Number Walkabout II

Audio Module & Headphones



Audio modul includes weatherproof enclosure and fits between pole and camera.

- Internal microphone with high gain amplifier and volume limiting compression circuit
- 1.2 in. D x 2 in. L/0.2 lbs

Part Number AAM

Universal Chest Harness



Universal, adjustable chest harness.

Part Number WUH

Carrying Case



Rugged carrying case

Part Number A-CASE

Batteries, Charger and Adapter



- 2 NiMH rechargeable batteries
- Battery charger
- Right angle adapter for pole

Part Numbers BAT-2, R-FNS, WBC

Alternate Display Configurations



Video Monocle



Standard Walkabout



Tandem View

